

MAXCIS 772-RT

Two Component, Polyurethane Based Adhesive

DEFINITION:

- It is a flexible, solvent-free floor adhesive.
- Self leveling
- It is resistant to outdoor conditions.
- It has high adhesion strength.

USAGE AREAS:

- Bonding SBR and EPDM tiles and rolls to the floor
- Bonding artificial grass to the floor

SURFACE PREPARATION:

- The surface must be solid and of sufficient strength.
- The application surface must be clean and dry. There should be no rust, dust, oil and water.

APPLICATION:

- After Component A is mixed with a low speed mixer, component B is added at the specified rate and mixing continues until a homogeneous mixture is obtained.
- The prepared mixture is applied to the surface with a notched trowel.
- Without delay, the products to be bonded are placed on the adhesive and pressed to ensure good adhesion.



TECHNICAL SPECIFICATIONS:

Test Name	Unit	Value
Density of Mixture	g/cm ³	1,70
Pot Life	minute	30-40
Curing Time	hour	1-1,5

CONSUMPTION:

- Depending on the surface structure, consumption is 0.80-1.00 kg/m².

PACKAGING:

- Component A 21 kg/plastic bucket, Component B 3 kg/metal can. Total 24 kg/set

SELF LIFE AND STORAGE:

It should be stored in original, unopened and undamaged packages, in dry environments between 15°C-25°C, away from direct sunlight. Shelf life is 12 months.

WARNING:

- Before using the product, read the MSDS form carefully and follow the written instructions.
- Personal protective equipment should be used during application.
- There must be sufficient air circulation in the application area.
- Give empty packages to organizations authorized to collect hazardous waste.