

# MAXCIS TAPE-BT

## ***Self-Adhesive Butyl Tape***

### **DEFINITION:**

- It is a flexible insulation tape whose upper part is covered with felt or aluminum.
- It adheres very well to all common surfaces.
- It has permanent elasticity.
- It is highly compatible with the liquid waterproofing materials to be applied on it.
- It provides sealing by covering the recessed surfaces very well.
- It is UV resistant.
- Can be applied on horizontal and vertical surfaces.



### **USAGE AREAS:**

- Floor-wall junction chamfers
- On surfaces at risk of cracking
- At the junction points of rain drains with concrete
- Insulation details of bathroom, WC and kitchen wet areas
- At the junction points of roof water channels
- At the junction points of chimney and floor

### **SURFACE PREPARATION:**

- The application surface must be clean and dry. There should be no rust, dust, oil and water.
- Weak layer and mortar residues on the concrete surface should be cleaned by mechanical grinding method.

### **APPLICATION:**

- After the protective paper on the back is removed, the product is carefully adhered to the surface to be applied.
- By pressing with a roller or hand, it is ensured that it fully adheres to every point of the application surface.
- Care should be taken to avoid potting on the surface.

### **PACKAGING:**

- 20 meters/rulo

**DIMENSIONS:**

- 5 cm, 10 cm, 15 cm, 20 cm wide

**SELF LIFE AND STORAGE:**

- It should be stored in original, unopened and undamaged packages, in dry environments between 15°C-25°C, away from direct sunlight. Shelf life is 12 months.