

MAXCIS TAPE-CT

TPE Based Chamfer Tape

DEFINITION:

- It is a chamfer band with high elasticity and a felt or mesh carrier.
- It can be produced in different colors and sizes.
- Compatible with all waterproofing materials.

USAGE AREAS:

- At the junctions of the floor and the wall
- Corner turns in wet area insulation
- Crack repair

SURFACE PREPARATION:

- The application surface must be clean and dry. There should be no rust, dust, oil and water.
- Weak layer and mortar residues on the concrete surface should be cleaned by mechanical abrasion method.



APPLICATION:

- Chamfer tape is adhered to the application surface with cement-based mortar.
- The adhesive mortar must be waited to dry completely before applying it.

TECHNICAL SPECIFICATIONS:

Test Name	Unit	Standard	Value
Chemical structure	-	-	TPE + felt/mesh
Width	mm	-	120/70
Thickness	mm	-	0,50 ± 0,05
Service Temperature	°C	-	-40 / +90
Hardness (Shore A)	-	ISO 868	65-70
Width Elongation	%	EN-ISO 527-3	145
Water Pressure Resistance	bar	EN 1928	>1,5

PACKAGING: 50 meters/roll

SELF LIFE AND STORAGE:

It should be stored in original, unopened and undamaged packages, in dry environments between 15°C-25°C, away from direct sunlight. Shelf life is 12 months.